



ENC PAD

Premanufactured Enclosure Pad

Lightweight, nestable, stacking, impact resistant and textured 3" deep pads, (surface deck 5/16" thickness) Pads are constructed of monolithic structural foam, molded from polyolefin plastic with ultraviolet stabilization and anti-oxidant properties, (some EncPad™ kits utilize two or more pads). Pads will not chip and will withstand abuse from gas powered lawn edgers. Full depth, 3/8" thick monolithic reinforcing ribs, formed 6" on centers, maximum EncPads™ accept self tapping screws and bolts for hinges and PadLok™ equipment. Hinge areas reinforced as needed. Anchor bolts for standard locking brackets and Lock Shield Brackets fastened completely through reinforcing ribs so that they cannot be pulled out.

MODEL	TYPE	ENC PAD™ DIMENSIONS*
EP-5 . . .	1 pc	24" w x 24" l
EP-1	1 pc	24" w x 36" l
EP-2	1 pc	24" w x 42" l
EP-3	1 pc	24" w x 48" l
EP-4	2 pc	30" w x 60" l
EP-5	2 pc	36" w x 84" l
EP-6	2 pc	36" w x 96" l
EP-7	2 pc	50" w x 120" l
EP-9***	3 pc	50" w x 180" l
EP-10***	4 pc	50" w x 240" l

FROST GUARD

Insulated Blankets

FrostGuard™ Insulated Blankets are an extremely low cost "insurance policy" designed to protect your customer's backflow assembly for the occasional late fall / early spring cold spells which could otherwise result in freezing damage or destruction to exposed backflow assemblies. And the FrostGuard™ is a "set it and forget it" installation since you can leave it on year round.

To order FrostGuard™ Insulated Blankets for 2½" through 10" assemblies, please provide factory with your backflow assembly dimensions, including width of units to be covered.

MODEL # for R-13 MATERIAL	MODEL # for R-30 MATERIAL	FROSTGUARD BLANKET INTERIOR DIMENSIONS
FG-5	FG-5 / R-30	10" l x 16½" h
FG-1	FG-1 / R-30	22" l x 22½" h
FG-2	FG-2 / R-30	30" l x 22½" h
FG-3	FG-3 / R-30	40" l x 22½" h
FG-3.5	FG-3.5 / R-30	40" l x 28½" h
FG-4	FG-4 / R-30	46" l x 28½" h

FrostGuard™ Specifications

Constructed of Calliope Polymeric Resin Coated Polyester Fabric, which is a 100% polyester plain weave with heat sealable pigmented coating.

5 year UV resistance warranty when used inside GuardShack™ enclosures.

Insulation is compressed fiberglass, available with standard R-value of R-13 and R-30

Machine stitched with reinforced metal grommet on bottom for installation of padlock when used without a GuardShack™ enclosure. Inside a GuardShack™ simply wire any grommet closed to help seal blanket bottom.

Any RP relief valve discharge venting is un-impeded, even when Blanket sides or bottom edges are wired together for best insulation protection

All FrostGuard™ blankets are sized to fit the appropriate GuardShack™ enclosure